

## High-Efficiency Longitudinal Diode Bar Pumping of Solid-State Lasers


15 March 1994

Prepared by

T. S. ROSE, J. S. SWENSON, and R. A. FIELDS  
Electronics Technology Center  
Technology Operations

Prepared for

SPACE AND MISSILE SYSTEMS CENTER  
AIR FORCE MATERIEL COMMAND  
2430 E. El Segundo Boulevard  
Los Angeles Air Force Base, CA 90245



Engineering and Technology Group

19950216 014

APPROVED FOR PUBLIC RELEASE;  
DISTRIBUTION UNLIMITED



**THE AEROSPACE  
CORPORATION**  
El Segundo, California


This report was submitted by The Aerospace Corporation, El Segundo, CA 90245-4691, under Contract No. F04701-88-C-0089 with the Space and Missile Systems Center, 2430 E. El Segundo Blvd., Suite 6037, Los Angeles AFB, CA 90245-4687. It was reviewed and approved for The Aerospace Corporation by T. A. Galantowicz, Principal Director, Electronics Technology Center. Maj. James J. Rosolanka was the project officer for the Mission-Oriented Investigation and Experimentation (MOIE) program.

This report has been reviewed by the Public Affairs Office (PAS) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nationals.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.



JAMES J. ROSOLANKA, MAJ, USAF  
Director, Space Systems Acquisition



NATHAN A. KIRBY  
Deputy, Industrial & International Division  
Plans and Programs Directorate  
Phillips Laboratory

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 15 March 1994		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE  High-Efficiency Longitudinal Diode Bar Pumping of Solid-State Lasers			5. FUNDING NUMBERS  F04701-88-C-0089	
6. AUTHOR(S)  Rose, Todd S.; Swenson, James S.; and Fields, Renny A.				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The Aerospace Corporation Technology Operations El Segundo, CA 90245-4691			8. PERFORMING ORGANIZATION REPORT NUMBER  TR-92(2925)-1	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Space and Missile Systems Center Air Force Materiel Command 2430 E. El Segundo Blvd. Los Angeles Air Force Base, CA 90245			10. SPONSORING/MONITORING AGENCY REPORT NUMBER  SMC-TR-95-5	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  A longitudinal diode bar pumping scheme for a solid state laser has been conceived which can concentrate tens of watts of pump power into a 250 $\mu$ m spot with nearly 100% efficiency.				
14. SUBJECT TERMS Diode pumping Microoptics Solid state laser			15. NUMBER OF PAGES 9	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	

## Contents

Abstract .....	2
Introduction .....	2
Results .....	2
Acknowledgments .....	3
References.....	5

## Figures

1. Illustration of adjacent lenses in array and illumination by diode bar.....	3
2. Photograph of sample 300 $\mu\text{m}$ diameter GaP lenses on 100 and 500 $\mu\text{m}$ centers .....	4
3. Far field intensity image of microlens collimated SDL-5410 diode laser.....	4
4. Diode bar plus microlens array configured to longitudinally pump a solid state laser.....	5

<b>Accession For</b>			
NTIS GRA&I	<input checked="" type="checkbox"/>		
DTIC TAB	<input type="checkbox"/>		
Unannounced	<input type="checkbox"/>		
Justification			
By _____			
Distribution/_____			
<b>Availability Codes</b>			
<b>Dist</b>	<b>Avail and/or Special</b>		
A-1	<table border="1" style="width: 100%; height: 40px; border-collapse: collapse;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%;"></td> </tr> </table>		

# High-Efficiency Longitudinal Diode Bar Pumping of Solid-State Lasers

T. S. Rose, J. S. Swenson, and R. A. Fields

*The Aerospace Corporation, Electronics Technology Center, PO Box 92957,  
Los Angeles, California 90009*

## Abstract

A longitudinal diode bar pumping scheme for a solid state laser has been conceived which can concentrate tens of watts of pump power into a 250  $\mu\text{m}$  spot with nearly 100% efficiency.

## Introduction

For many years longitudinal pumping of lasers has proven to be an effective method for maximizing the conversion of pump photons to laser photons. Sipes [1] demonstrated that a collimated phase coupled diode laser array could be axially focused into a Nd:YAG crystal to yield an overall efficient device. At higher diode pump powers (1 watt) this approach was shown to give consistently better than 60% optical conversion efficiency for  $\text{Nd}^{3+}(^4\text{F}_{3/2} \rightarrow ^4\text{I}_{11/2})$  lasing [2]. As one method to reach still higher powers and retain efficiency, Fan et al. [3] showed that several diode lasers, similar to those used by Sipes, could be separately collimated and simultaneously focused by a single large aperture lens to one spot within the laser mode. Because of cost and practicality issues, most higher power diode pumped lasers have been pumped by diode laser bars. Attempts to efficiently collimate diode bars containing groups of phase coupled arrays (or large area stripes) have been limited due to the complex wavefront of the emitters.

The concept presented here is based on the implementation of a new diode bar containing uncoupled index guided single transverse mode diode lasers with a matching microlens array. The end result is efficient (nearly 100%) collection and collimation of the diode bar laser light. We have developed a stand-alone array of microlenses which are spaced on the identical centers as the individual single mode lasers so that the

output of each element of the bar is collimated. The important distinction between the present technique and the other efforts alluded to above is that the emission of each diode laser element can be collimated by a single optic since the wavefront is nearly planar. The more traditional gain guided wide stripes or phase coupled arrays typically require separate axis collimation to reach diffraction limited far field images. The present approach stresses the ultimate packing density of single mode lasers in a bar format and fabrication techniques for high quality microoptics.

## Results

To test the bar-microlens array concept, an array of microlenses was designed to match the divergence properties of the Spectra Diode Labs 5410 single mode laser. This laser has approximately a 3:1 out-of-plane: in-plane aspect ratio and a divergence of  $\sim 900$  mrad ( $1/e^2$  full angle) in the former direction. Because only one-third of a lens would be illuminated along the array axis, the lenses were configured to overlap by one-third with each other to maximize the packing density (see Fig. 1) and ultimately the power per collimated bar. Clearly, the diode elements could be increased in power or more closely spaced. However, the diode spacing is limited by the effective potential for cross coupling between elements. Furthermore, if the element spacing is increased, the microlens diameter can be increased, thereby relaxing the diode-to-lens registration tolerance. At present, the SDL-5410 produces reliable output up to 100 mW. The design which follows below effectively combines all the above design criteria.

Liau et al. [4] recently demonstrated microlens technology with InP and GaP, whereby a wedding cake-like structure could be smoothed into a lens via




Figure 1. Illustration of adjacent lenses in array and illumination by diode bar.

mass transport. To improve lens repeatability and accuracy, the wedding cake layers on GaP were formed by ion milling as opposed to chemical etching. Additionally, the lens size and finish were enhanced by the development of a novel encapsulation approach for the mass transfer process. Using the above techniques we have fabricated 150  $\mu\text{m}$  fl hyperbolic lenses (160  $\mu\text{m}$  diameter) on 200, 100 and 50  $\mu\text{m}$  centers and 300  $\mu\text{m}$  fl (300  $\mu\text{m}$  diameter) hyperbolic lenses on 100 and 500  $\mu\text{m}$  centers. A photograph of our 300  $\mu\text{m}$  lens array chosen for the ultimate bar collimation is shown in Fig. 2. One single mode diode laser (SDL-5410) was used to test the optical integrity of this microlens array. The 5410 optical divergence was measured to be  $28.8^\circ$  and  $6.6^\circ$  FWHM in the vertical and horizontal directions respectively. After correcting for the fresnel losses nearly 100% of the light from the microlens collimated 5410 was collected in a single uniform spot (see Fig. 3). This result demonstrates that there is minimal distortion caused by the boundary points between the overlapping lenses. The subsequent vertical and horizontal divergences were 3.0 and 11.7 mrad, which are 1.2 and 1.1 times the respective diffraction limits. This assumes that the diode is a pure gaussian output and attributes the small imperfection of the beam to the lens.


To date, several efforts have been performed to antireflection coat the GaP lenses. R. Waarts of Spectra

Diode Labs has coated GaP for 950 nm with  $\text{Al}_2\text{O}_3$  and achieved 98% transmission [5]. Our best effort has been 94% transmission at 808 nm with aluminum oxide. Efforts are currently being pursued to get a better index match to the GaP at 808 nm for higher transmission.


The successful collimation of the single diode device suggests that a 1 cm diode bar can be fashioned with an array of 100 single mode 5410-like 100 mW devices spaced on 100  $\mu\text{m}$  centers to yield a 10 watt collimated device. When such a device is configured as shown in Fig. 4, a 2.1 cm fl focusing lens should theoretically yield a focused spot about 80 by 240  $\mu\text{m}$ . Our tests with the single laser diode, microlens, and focusing lens results in transmission through 100, 200, and 500  $\mu\text{m}$  apertures of 0.8, 0.9, and 1.0, respectively. A diode bar fitting the above specifications is currently being fabricated.

#### Acknowledgments

The technical assistance of C. L. Fincher is gratefully acknowledged. This work was supported under the Government Contract No. FO4701-88-C-0089 awarded by the Department of the Air Force.



(a)



(b)

Figure 2. Photograph of sample  $300\text{ }\mu\text{m}$  diameter GaP lenses on  $100$  and  $500\text{ }\mu\text{m}$  centers: (a) focused on the microlenses, (b) focused on the images formed above the microlenses.




Figure 3. Far field intensity image of microlens collimated SDL-5410 diode laser. The plots on both sides of the figure represent the intensity profiles for the two orthogonal axes.




Figure 4. Diode bar plus microlens array configured to longitudinally pump a solid state laser.

#### References

1. D. L. Sipes, "Highly efficient neodymium:yttrium aluminum garnet laser end pumped by a semiconductor laser array," *Appl. Phys. Lett.* **47**, 74 (1985).
2. R. A. Fields, T. S. Rose, M. E. Innocenzi, H. T. Yura, and C. L. Fincher, "Diode laser end-pumped neodymium lasers: the road to higher powers," in *Tunable Solid State Lasers*, Vol. 5 of the OSA Proceeding Series, M. L. Shand and H. P. Jenssen, eds. (Optical Society of America, Washington, D. C., 1989), pp. 301-308.
3. T. Y. Fan, A. Sanchez, and W. E. DeFeo, "Scalable, end-pumped, diode-laser-pumped laser," *Opt. Lett.*, **14**(19), 1057, (1989).
4. Z. L. Liao, V. Diadiuk, J. N. Walpole, and D. E. Mull, "Gallium phosphide microlenses by mass transport," *Appl. Phys. Lett.* **55**(2), 97, (1989).
5. R. Waarts, personal communication.



## TECHNOLOGY OPERATIONS

The Aerospace Corporation functions as an "architect-engineer" for national security programs, specializing in advanced military space systems. The Corporation's Technology Operations supports the effective and timely development and operation of national security systems through scientific research and the application of advanced technology. Vital to the success of the Corporation is the technical staff's wide-ranging expertise and its ability to stay abreast of new technological developments and program support issues associated with rapidly evolving space systems. Contributing capabilities are provided by these individual Technology Centers:

**Electronics Technology Center:** Microelectronics, solid-state device physics, VLSI reliability, compound semiconductors, radiation hardening, data storage technologies, infrared detector devices and testing; electro-optics, quantum electronics, solid-state lasers, optical propagation and communications; cw and pulsed chemical laser development, optical resonators, beam control, atmospheric propagation, and laser effects and countermeasures; atomic frequency standards, applied laser spectroscopy, laser chemistry, laser optoelectronics, phase conjugation and coherent imaging, solar cell physics, battery electrochemistry, battery testing and evaluation.

**Mechanics and Materials Technology Center:** Evaluation and characterization of new materials: metals, alloys, ceramics, polymers and their composites, and new forms of carbon; development and analysis of thin films and deposition techniques; nondestructive evaluation, component failure analysis and reliability; fracture mechanics and stress corrosion; development and evaluation of hardened components; analysis and evaluation of materials at cryogenic and elevated temperatures; launch vehicle and reentry fluid mechanics, heat transfer and flight dynamics; chemical and electric propulsion; spacecraft structural mechanics, spacecraft survivability and vulnerability assessment; contamination, thermal and structural control; high temperature thermomechanics, gas kinetics and radiation; lubrication and surface phenomena.

**Space and Environment Technology Center:** Magnetospheric, auroral and cosmic ray physics, wave-particle interactions, magnetospheric plasma waves; atmospheric and ionospheric physics, density and composition of the upper atmosphere, remote sensing using atmospheric radiation; solar physics, infrared astronomy, infrared signature analysis; effects of solar activity, magnetic storms and nuclear explosions on the earth's atmosphere, ionosphere and magnetosphere; effects of electromagnetic and particulate radiations on space systems; space instrumentation; propellant chemistry, chemical dynamics, environmental chemistry, trace detection; atmospheric chemical reactions, atmospheric optics, light scattering, state-specific chemical reactions and radiative signatures of missile plumes, and sensor out-of-field-of-view rejection.